

DTI CLEAN TUBING & PIPE STANDARD

For Semiconductor / Ultra high vacuum

No.	Outside Diameter (mm)	Wall thickness (mm)											
		0.89	1.0	1.2	1.24	1.65	2.1	2.8	3.0	3.4	4.0	4.5	5.0
1	6.35	●	●										
2	9.53	●	●										
3	10.5		●	●									
4	12.7		●		●								
5	13.8			●		●							
6	15.9		●		●								
7	17.3			●		●							
8	19.05				●	●							
9	21.7					●	●						
10	25.4				●	●							
11	27.2					◎	●						
12	34.0					◎		●					
13	42.7					◎		●					
14	48.6					◎		●					
15	60.5					◎		●					
16	76.3						◎		●				
17	89.1						◎		●				
8	101.6						◎		●				
19	114.3						◎		●				
20	139.8							◎		◎			
21	165.2							◎		◎			
22	216.3							◎			◎		
23	267.4								◎		◎		
24	318.5									◎		◎	
25	355.6										◎		◎

For Sanitary / BPE/ Ultra High Vacuum

No.	Outside Diameter (mm)	Wall Thickness (mm)	
1	6.35	1.0	●
2	9.53	1.0	●
3	12.7	1.65	●
4	15.9	1.65	●
5	19.05	1.65	●
6	25.4	1.65	◎
7	31.8	1.65	◎
8	38.1	1.65	◎
9	50.8	1.65	◎
10	63.5	1.65	◎
11	76.2	1.65	◎
12	89.1	2.1	◎
13	101.6	2.1	◎
14	114.3	2.1	◎
15	152.4	2.8	◎



● : Seamless stainless steel tubing & pipe

◎ : Welded or Seamless stainless steel tubing & pipe